KSU.P0206 14

CLAIMS

What is claimed is:

1	1.	A method for generating random numbers comprising:
2		providing a liquid crystal cell containing a liquid crystal material between
3		substrates, each substrate having a facing electrode;
4		applying a potential difference across said electrodes;
5		measuring at least one physical property of said liquid crystal material to
6		generate a plurality of reading measurements; and
7		setting bits based on said plurality of reading measurements to generate a
8		sequence of random numbers.
1	2.	The method of claim 1, wherein said at least one physical property is selected from
2		the group consisting of light absorbed by the liquid crystal, light transmitted by the
3	•	liquid crystal, light reflected by the liquid crystal, and the amount of electric current
4		traversing the liquid crystal.
1	3.	The method of claim1, further comprising
2		first measuring said at least one physical property to generate a baseline
3		measurement;
4		subsequently measuring said at least one physical property to generate a
5		plurality of reading measurements; and
6		setting said bits based on a comparison of said baseline measurement to said
7		plurality of reading measurements.
1	4.	The method of claim 1, wherein said liquid crystal material comprises nematic liquid
2		crystal.
1	5.	The method of claim 1, wherein said applying step causes the liquid crystal material
2		to undergo a chaotic turbulent flow.
1	6.	The method of claim 1, wherein said at least one physical property comprises a
2		plurality of light sources directing light toward said liquid crystal cell and a like

8

1

KSU.P0206 15 plurality of light detectors to measure properties of the light after impinging said 3 4 liquid crystal cell. 7. An apparatus for the generation of random numbers comprising: 1 a pair of opposed substrates containing a layer of liquid crystal therebetween 2 3 each said substrate having an electrode facing the other said substrates; a power supply applying an electric potential across said electrodes to drive 4 5 said liquid crystal into a chaotic flow; at least one device for measuring a physical property of said layer of liquid 6 7 crystal which generates physical property measurements after an electric potential is applied; and 8 9 an interface in communication with said device for measuring a physical property, wherein said interface digitizes said physical property measurements to 10 11 generate a random number. The apparatus according to claim 7, further comprising: 1 8. 2 a computer program connected to said interface, wherein said computer 3 program processes said digitized measurements into random numbers for use in encrypting data. 4 The apparatus according to claim 7, wherein said layer of liquid crystal is a nematic 1 9. 2 material. A method of encrypting data comprising: 1 10. 2 providing a liquid crystal cell responsive to an electrical stimulus; applying an electrical stimulus to said liquid crystal cell; 3 measuring at least one physical property of said liquid crystal cell to generate 4 5 a baseline measurement: setting a plurality of bits based on said baseline measurement so as to generate 6 7 a sequence of random numbers; and

11. The method according to claim 10, further comprising:

using said sequence of random numbers to generate an encryption key.

KSU.P0206

6

7

8

applying said encryption key to data transmitted by a computing device.

1 12. The method according to claim 10 further comprising
2 subsequently measuring the at least one physical property of said liquid crystal
3 cell to generate a plurality of reading measurements;
4 determining the difference between each of said reading measurements and the
5 baseline measurement; and

16

setting said plurality of bits based on differences between said plurality of reading measurements and said baseline measurement to generate said sequence of random numbers.